

Egco Magico 800

Description

Egco Magico 800 is a matt finish based on a modified acrylic emulsion with good hiding and whiteness for interior surfaces.

Technical Data

Viscosity	40-50 Sec Cup 8
Solid content	65±2%
Density	1.65±0.02gm/cm ³
Gloss	Matt
Coverage	6-9 m ² /kg (Dry film thickness 45-50 μ)

Product Features

- Alkali resistant;
- Easy to apply;
- Good leveling;
- Good whiteness;
- Good hiding power;

Substrates and surface preparation

Egco Magico 800 is recommended for application over bricks, plaster, concrete or cement surfaces.

All new or already painted surfaces should be free from dust, grease and waxes.

Application

New Surfaces

1. Apply Egco Sealer 851 in one coat;
2. Apply Egco Putty 850 in two cross layers;
3. Apply Egco Magico 800 in two coats after dilution with water (20 % dilution) to reach the application viscosity.

Old painted surface with oil or alkyd paints

1. Sand and remove dust;
2. Apply Egylac 2010 in one coat;
3. Apply Egco Magico 800 in two coats after dilution with water (15 % dilution) to reach the application viscosity.

Decorative Paints

Old painted surface with emulsion paints

1. Washing with water & liquid soap;
2. Rinse with water;
3. Apply Egco Sealer 851 in one coat;
4. Apply Egco Magico 800 as a top coat in two coats after dilution with water (20 % dilution) to reach the suitable application viscosity.

Drying time at 25 °C & 60% R.H

Initial drying time 1h

Recoating time 4h

Final drying time 6h

Tools

Brush, roller or airless spray gun

Cleaner: water

Color

White and can be colored

Expiry

Two years from production date if stored in original sealed container at normal temperature.

Storage

Keep away from direct sun light.